

# 600N Crystal Hose Food Quality

**FR** Tuyau en PVC souple de qualité alimentaire  
**ES** Manguera de PVC de calidad alimentaria  
**DE** Lebensmittelqualität PVC-Schlauch  
**RU** Шланг ПВХ для пищевой промышленности



Single layer of transparent soft PVC, not reinforced



**-10°C | +60°C**  
TEMPERATURE RANGE

**FOOD QUALITY**  
10/2011 A, B, C, D1

**EN** Soft PVC hose in single layer, for transporting liquids or air with industrial, pharmaceutical or food applications.

**FR** Tuyau en PVC souple en une seule couche, destiné au transport de liquides ou d'air dans des applications industrielles, pharmaceutiques ou alimentaires.

**ES** Manguera de PVC suave de una sola capa, diseñada para transportar líquidos o aire en aplicaciones industriales, farmacéuticas o alimentarias.

**DE** Weicher PVC-Schlauch in Einzelschicht, geeignet für den Transport von Flüssigkeiten oder Luft in industriellen, pharmazeutischen oder Lebensmittel-Anwendungen.

**RU** Мягкий ПВХ-шланг однослойной конструкции для транспортировки жидкостей или воздуха в промышленных, фармацевтических или пищевых приложениях.



code	mm	mm	gr/m	bar	bar	m
V600N00406	4	6	19	4	12	25/50/100
V600N00407	4	7	35	9	27	25/50/100
V600N00507	5	7	23	4	12	25/50/100
V600N00608	6	8	28	4	12	25/50/100
V600N00609	6	9	45	5	15	25/50/100
V600N00610	6	10	62	9	27	25/50/100
V600N00612	6	12	104	11	33	25/50/100
V600N00710	7	10	57	4	12	25/50/100
V600N00711	7	11	68	8	24	25/50/100
V600N00811	8	11	55	4	12	25/50/100
V600N00812	8	12	78	7	21	25/50/100
V600N00912	9	12	61	3	9	25/50/100
V600N00913	9	13	84	5	15	25/50/100
V600N01013	10	13	66	4	12	25/50/100
V600N01014	10	14	95	6	18	25/50/100
V600N01016	10	16	151	7	21	25/50/100
V600N01216	12	16	110	4	12	25/50/100
V600N01319	13	19	184	6	18	25/50/100
V600N01418	14	18	125	4	12	25/50/100
V600N01519	15	19	132	4	12	25/50/100
V600N01620	16	20	140	2,5	7,5	25/50/100
V600N01621	16	21	177	3	9	25/50/100
V600N01823	18	23	198	3	9	25/50/100
V600N01924	19	24	210	3	9	25/50/100
V600N01925	19	25	253	3	9	25/50/100
V600N02025	20	25	220	2,5	7,5	25/50/100
V600N02026	20	26	264	3	9	25/50/100
V600N02228	22	28	290	3	9	25/50/100
V600N02230	22	30	395	4	12	25/50/100
V600N02531	25	31	324	2,5	7,5	25/50/100
V600N02533	25	33	445	3,5	10,5	25/50/100

\* Working and bursting pressure valid at 20°C / Pression de fonctionnement et limite, à 20° C / Presión de trabajo y estallido válida a 20°C / Betriebsdruck und Berstdruck gültig bei 20°C / Рабочее давление и разрывное давление, при 20°C

\*\* Length tolerance +/- 5% / Tolérance de longueur +/- 5% / Tolerancia de longitud +/- 5% / Längentoleranz +/- 5% / Допуск длины +/- 5%

\*\*\* Inner Diameter tolerance +/- 2% / Tolérance de diamètre interne +/- 2% / Tolerancia del diámetro interno +/- 2% / Toleranz des inneren Durchmessers +/- 2% / Допуск внутреннего диаметра +/- 2%

• Other colors are available against MOQ  
 • Autres couleurs et longueurs sont disponibles avec la quantité minimale d'un ordre  
 • Se ofrecen otros colores y longitudes contra una cantidad mínima de pedido  
 • Andere Farben sind gegen Mindestbestellmenge erhältlich  
 • В другом цвете возможен при соблюдении минимальных количеств к заказу

