

600POZ Oil Resistant Monolayer hose

ES Manguera monocapa resistente al aceite
DE Ölbeständiger Monolayer-Schlauch
RU Маслостойкий однослойный шланг



- EN This hose can be used for transportation of petroleum products and oils.
- ES Esta manguera puede utilizarse para el transporte de productos derivados del petróleo y aceites.
- DE Dieser Schlauch kann für den Transport von Erdölprodukten und Ölen eingesetzt werden.
- RU Этот шланг может использоваться для транспортировки нефтепродуктов и масел.



Single layer of transparent green soft PVC, not reinforced

	code	inch	mm	mm	gr/m	bar	bar	m
	V600POZ00305	1/8	3	5	15	3	9	50/100
	V600POZ00406	5/32	4	6	19	4	12	50/100
	V600POZ00407	5/32	4	7	35	9	27	50/100
	V600POZ00507	3/16	5	7	23	4	12	50/100
	V600POZ00508	3/16	5	8	38	5	15	50/100
	V600POZ00509	3/16	5	9	53	7	21	50/100
	V600POZ00608	1/4	6	8	28	4	12	50/100
	V600POZ00609	1/4	6	9	45	5	15	50/100
	V600POZ00610	1/4	6	10	62	9	27	50/100
	V600POZ00612	1/4	6	12	104	11	33	50/100
	V600POZ00710	1/4	7	10	57	4	12	50/100
	V600POZ00711	1/4	7	11	68	8	24	50/100
	V600POZ008/10,6	5/16	8	10.6	50	8	24	50/100
	V600POZ00811	5/16	8	11	55	4	12	50/100
	V600POZ00812	5/16	8	12	78	7	21	50/100
	V600POZ00912	3/8	9	12	61	3	9	50/100
	V600POZ00913	3/8	9	13	84	5	15	50/100
	V600POZ01013	3/8	10	13	66	4	12	50/100
	V600POZ01014	3/8	10	14	95	6	18	50/100
	V600POZ01016	3/8	10	16	151	7	21	50/100
	V600POZ01216	1/2	12	16	110	4	12	50/100
	V600POZ01217	1/2	12	17	132	5	15	50/100
	V600POZ01319	1/2	13	19	184	6	18	50/100
	V600POZ01418	9/16	14	18	125	4	12	50/100
	V600POZ01419	9/16	14	19	153	4	12	50/100
	V600POZ01519	5/8	15	19	132	4	12	50/100
	V600POZ01620	5/8	16	20	140	2.5	7,5	50/100
	V600POZ01621	5/8	16	21	177	3	9	50/100
	V600POZ01622	5/8	16	22	215	4	12	50/100
	V600POZ01823	11/16	18	23	198	3	9	50/100
	V600POZ01824	11/16	18	24	240	4	12	50/100
	V600POZ01924	3/4	19	24	210	3	9	50/100
	V600POZ01925	3/4	19	25	253	3	9	50/100
	V600POZ02025	13/16	20	25	220	2.5	7.5	50/100
	V600POZ02026	13/16	20	26	264	3	9	50/100
	V600POZ02027	13/16	20	27	310	4	12	50/100
	V600POZ02228	7/8	22	28	290	3	9	50/100
	V600POZ02230	7/8	22	30	395	4	12	50/100
	V600POZ02531	1	25	31	324	2.5	7.5	50/100
	V600POZ02533	1	25	33	445	3.5	10.5	50/100
	V600POZ05060	2	50	60	1042	2.5	7.5	50/100

* Working and bursting pressure valid at 20°C/ Pression de fonctionnement et limite, à 20° C / Presión de trabajo y estallido válida a 20°C / Betriebsdruck und Berstdruck gültig bei 20°C / Рабочее давление и разрывное давление, при 20°C

** Length tolerance +/- 5% / Tolérance de longueur +/- 5% / Tolerancia de longitud +/- 5% / Längentoleranz +/- 5% / Допуск длины +/- 5%

*** Inner Diameter tolerance +/- 2% / Tolérance de diamètre interne +/- 2% / Tolerancia del diámetro interno +/- 2% / Toleranz des inneren Durchmessers +/- 2% / Допуск внутреннего диаметра +/- 2%